

# Material Safety Data Sheet

CS: 1.4.93

Page: 1 of 4

Infosafe No™ LPZDW Issue Date : September 2010 ISSUED by INTERLUB

Product Name **SAE 40 API CF-2**

Not classified as hazardous

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** SAE 40 API CF-2  
**Company Name** International Lubricant Distributors Pty. Ltd. (ABN 79 139 276 887)  
**Address** Suite 28 Level 3, 22 Railway Rd Subiaco  
WA 6904 Australia  
**Emergency Tel.** 1300 558 939  
**Telephone/Fax Number** Fax: +61 8 9381 1788  
**Recommended Use** Engine lubricating oil.  
**Other Information** Waitomo Lubricants Limited (GST 104255744)  
15 Ellis Street, Frankton, Hamilton  
PO Box 5125, Hamilton 3242  
Emergency Tel. 07 847 0829 (24 Hrs)  
Tel. 07 847 0829  
Fax. 07 846 0032

## 2. HAZARDS IDENTIFICATION

**Hazard Classification** Not classified as hazardous  
Australia:  
Not classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).  
Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.  
New Zealand:  
Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.  
Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.  
**Risk Phrase(s)** Not classified as hazardous  
**Safety Phrase(s)** S24/25 Avoid contact with skin and eyes.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>
	Mineral Oil	Not available	90-95 %
	Additive	-	5-10 %

## 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention.  
**Ingestion** Do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop seek medical attention.  
**Skin** Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.  
**Eye** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and persist seek medical attention.  
**First Aid Facilities** Eyewash and normal washroom facilities.  
**Advice to Doctor** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** Use carbon dioxide, dry chemical or foam.  
**Hazards from Combustion Products** Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide and oxides of sulphur.

# Material Safety Data Sheet

CS: 1.4.93

Page: 2 of 4

Infosafe No™ LPZDW Issue Date : September 2010 ISSUED by INTERLUB

Product Name **SAE 40 API CF-2**

Not classified as hazardous

**Specific Hazards** Combustible liquid. This product will readily burn under fire conditions.

**Precautions in connection with Fire** Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

**Unsuitable Extinguishing Media** Do not use water jet.

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures** Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

## 7. HANDLING AND STORAGE

**Precautions for Safe Handling** Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.

**Conditions for Safe Storage** Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

**Storage Regulations** Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well-ventilated area away from naked flames, sparks and other sources of ignition.

**Handling Temperatures** Should not exceed 176°C.

**Storage Temperatures** Should be between 0-50°C.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**National Exposure Standards** No exposure standards have been established for this material. As with all chemicals, exposure should be kept to the lowest possible levels. The exposure limits for oil mist are as follows:  
Australian National Occupational Health And Safety Commission (NOHSC) exposure standards:  
Oil mist TWA 5 mg/m<sup>3</sup>  
New Zealand Workplace Exposure Standards (OSH):  
Oil mist TWA 5 mg/m<sup>3</sup> STEL 10 mg/m<sup>3</sup>  
TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.  
STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

**Biological Limit Values** No biological limits allocated.

# Material Safety Data Sheet

CS: 1.4.93

Page: 3 of 4

Infosafe No™ LPZDW	Issue Date : September 2010	ISSUED by INTERLUB
--------------------	-----------------------------	--------------------

Product Name **SAE 40 API CF-2**

Not classified as hazardous

<b>Engineering Controls</b>	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Body Protection</b>	Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Brownish liquid.
<b>Odour</b>	Characteristic mineral oil.
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	Not available
<b>Solubility in Water</b>	Negligible
<b>Specific Gravity</b>	0.8936
<b>pH Value</b>	Not available
<b>Vapour Pressure</b>	<0.5 Pa at 20°C
<b>Pour Point</b>	-15°C
<b>Flash Point</b>	>225°C
<b>Flammability</b>	Combustible
<b>Auto-Ignition Temperature</b>	>300°C
<b>Flammable Limits - Lower</b>	1.0
<b>Flammable Limits - Upper</b>	6.0
<b>Kinematic Viscosity</b>	154 cSt at 40°C 15.3 cSt at 100°C

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Extremes of temperature and direct sunlight. Heat and other sources of ignition.
<b>Incompatible Materials</b>	Strong oxidizing agents, strong acids.
<b>Hazardous Decomposition Products</b>	Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide and oxides of sulphur.
<b>Hazardous Reactions</b>	Will react with incompatibles.
<b>Hazardous Polymerization</b>	Will not occur.

# Material Safety Data Sheet

CS: 1.4.93

Page: 4 of 4

Infosafe No™ LPZDW	Issue Date : September 2010	ISSUED by INTERLUB
--------------------	-----------------------------	--------------------

Product Name **SAE 40 API CF-2**

Not classified as hazardous

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicology Information</b>	No toxicity data available for this product.
<b>Inhalation</b>	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
<b>Ingestion</b>	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
<b>Skin</b>	May be irritating to skin. The symptoms may include redness, itching and swelling.
<b>Eye</b>	May be irritating to eyes. The symptoms may include redness, itching and tearing.
<b>Chronic Effects</b>	Not available

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	No ecological data are available for this material.
<b>Persistence / Degradability</b>	Not readily biodegradable.
<b>Mobility</b>	Insoluble in water, absorbed by soil and will not be mobile.
<b>Bioaccumulative Potential</b>	Has the potential to bioaccumulate.
<b>Environ. Protection</b>	Prevent this material entering waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

<b>Disposal Considerations</b>	Dispose of waste according to applicable local and national regulations.
--------------------------------	--------------------------------------------------------------------------

## 14. TRANSPORT INFORMATION

<b>Transport Information</b>	Australia: Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
	New Zealand: Not classified as Dangerous Goods for transport according to the NZS 5433:2007 Transport of Dangerous Goods on Land.

## 15. REGULATORY INFORMATION

<b>Regulatory Information</b>	Australia: Not classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
<b>Poisons Schedule</b>	Not Scheduled
<b>National and or International Regulatory Information</b>	New Zealand: Not classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

## 16. OTHER INFORMATION

**Date of preparation or last revision of MSDS** MSDS Prepared: September 2010

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.